



Print Date:	07/08/2023	Specification Log Number			66M93A	
Specification & Product Information Sheet						
Product Name		1/4 Flexsil-Lid by Wrapmaster		Product Code	66M93A - Model Number FL-CC04	
Information	High grade silicon lid used on gastronorm trays or steam pans of same size. NSF Certified. Lip-Lock design, locks in freshness & reduces food waste with an airtight seal. Transportable, stackable, flexible, durable and can be reused multiple times making them environmentally friendly. Oven & microwave safe up to 220°C / 428°F. Freezer safe to -40°C / -40°F. The lids are easy to clean and disinfect in a commercial dishwasher.					
Labels Inner	N/A		Labels Outer	Outer labels should contain - Product description, Pack size, Product Code, Model Number, Dimensions, Gross Weight, Net Weight, Country of Origin, Barcode. Also Manufactured for Cofresco Foodservice, a division of Melitta UK Ltd.		
Country Of Origin & Manufacture	China		Barcode Single	Single Lid - 5023139669301	Other Information	
Packaging Inner Box	N/A		Barcode Pack	N/A	Note: EAN Code must be machine readable & food Safe icon to appear on carton.	
Packaging Outer Box	Plain brown packaging		Barcode Case	5023139669318		
Packing Instructions				Pallet Configuration		
12 Lids per Case.				Standard/CHEP Pallet - 25 Cases per layer, 8 Layers high, 200 Cases per pallet. Euro Pallet - 19 Cases per Layer, 8 Layers high, 152 Cases per pallet.		
Weights & Dimensions		Packaging Waste Weights (Approximate) (G)				
Single Product weight (G) (e.g. Foil sheet, bag, tray etc.)	135	Primary Packaging		Secondary	Secondary	Transit
Inner Weight (G)	N/A	Recycled Cardboard/Paper	14.24	80	0	0
Pack Weight (G)	N/A	Recycled Cardboard/paper Core	0	0	0	0
Case Weight (KG)	1.7	Plastic LDPE	3.5	0	0	0
Single Product Dimensions (CM)	16.8 x 5 x 34	Plastic PP	0	0	0	0
Inner Dimensions (CM) W x H x D	N/A	Plastic Blade	0	0	0	0
Pack Dimensions (CM) W x H x D	N/A	Metal Blade	0	0	0	0
Case Dimensions (CM) W x H x D	17 x 9 x 27	Instratat/Commodity Code			3924900090	
Pallet Wrapping						
Stretch wrapped secured to pallet, minimum of 8 revolutions						